



TECHNICAL DATA SHEET – OVERVIEW

Melville 60 Slabs

Dimensions (mm): 60 x 190 x 380
(Height x width x length) 60 x 380 x 380
60 x 380 x 570

Approximate weight: 10 kg to 30 kg

Colours: Range Margaux Beige, Range Scandina Grey, Rockland Black,
Range Newport Grey, Range Savannah Beige, Range Amber Beige
Range Shaded Grey, Range Habano Brown, Range Norvick Grey

Finish: Smooth

Physical properties

(CSA – Can A231.1 Precast Concrete Paving Slabs)

Flexural strength (min) to 28 days: 4.5 MPa
Scaling resistance (Freeze and thaw)
Loss of mass after 28 cycles: 300 g/m² (max)
Loss of mass after 49 cycles: 800 g/m² (max)
Compressive strength: N/A
Absorption: N/A
Dry density: N/A

Dimensional tolerances

Thickness: ± 3 mm
Length & width: -1 mm to + 2 mm
Warpage (max): 3 mm

Notes:

This product is for pedestrian application only.
This product can be installed on granular base only

Technical Services

Technical support offered by the Permacon's representatives and the engineering department.

Product samples are available upon request, see your representative.

Test report available upon request. This report is issued by our engineers and technicians following the test results at Permacon's laboratory.