





MELVILLE® 60 PAVER SMALL RECTANGLE



 Do not use vibrating plate

 **Techniseal Sand 1 Bag** - Approx. 103 ft² coverage

 **Vehicular** - Designed to withstand car traffic

 **Pedestrian** - Designed to withstand pedestrian traffic


MELVILLE® 60 PAVER SMALL RECTANGLE




	DIMENSIONS (MM)	DIMENSIONS (IN)
	60 x 190 x 380	2 3/8 x 7 1/2 x 15
Weight/unit	10 kg	22 lb
Units/area	13.89 units/m ²	1.29 units/ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	10.44 m²	12 Rows
Length/layer Soldier	2.28 lin. m	7.48 lin. ft
Length/cube Soldier	27.36 lin. m	89.76 lin. ft
Qty/cube	144 units	144 units
Weight/cube	1465 kg	3225 lb

CODES	COLOURS
PRESTIGE COLOURS	
12053044	Range Amber Beige
12052446	Rockland Black
12052448	Range Scandina Grey
STANDARD COLOUR	
12053043	Range Shaded Grey
Sold in full cubes only	
Can be double stacked	
Production location - Quebec	


TYPICAL ROW



LAYING PATTERNS



LINEAR PATTERN



HERRINGBONE PATTERN

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.
The Melville 60 slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.